



## CUDNER & O'CONNOR CO.

### Safety Data Sheet CC-006 CRYSTAL COAT PART 2

---

#### SECTION 1: Identification

##### 1.1 Product identifier

Product name	CC-006 CRYSTAL COAT PART 2
Product number	CC-006
Brand	CANDOC

##### 1.2 Other means of identification

Clear Printing Ink

##### 1.3 Recommended use of the chemical and restrictions on use

Uses : Printing Ink

##### 1.4 Supplier's details

Name	Cudner & O'Connor Co.
Address	4035 West Kinzie St Chicago, IL 60624 USA
Telephone	773-826-0200
Fax	773-826-0477
email	CANDOC1@AOL.COM

##### 1.5 Emergency phone number(s)

800-535-5053

---

#### SECTION 2: Hazard identification

##### 2.1 Classification of the substance or mixture

- Flammable liquids (chapter 2.6), Cat. 3
- Acute toxicity, dermal (chapter 3.1), Cat. 5
- Acute toxicity, inhalation (chapter 3.1), Cat. 5
- Acute toxicity, oral (chapter 3.1), Cat. 5
- Eye damage/irritation (chapter 3.3), Cat. 2A

##### 2.2 GHS label elements, including precautionary statements

Pictogram

**Safety Data Sheet**  
**CC-006 CRYSTAL COAT PART 2**



**Signal word**

**Danger**

**Hazard statement(s)**

H226	Flammable liquid and vapor
H303	May be harmful if swallowed
H313	May be harmful in contact with skin
H319	Causes serious eye irritation
H333	May be harmful if inhaled

**Precautionary statement(s)**

P210	Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting and equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P312	IF INHALED: Call a POISON CENTER or doctor if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use foam,alcohol foam,CO2, dry chemical,water fog to extinguish.
P403+P235	Store in a well ventilated place. Keep cool.
P501	Dispose of in accordance with local, county, state, provincial and federal regulations.

**2.3 Other hazards which do not result in classification**

---

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**Hazardous components**

**1. POLYESTER POLYMER**

Concentration 70 - 80 %

**2. 2-methoxy-1-methylethyl acetate**

Concentration 20 - 25 %

Other names / synonyms 2-Propanol, 1-methoxy-, 2-acetate

EC no. 203-603-9

CAS no. 108-65-6

Index no. 607-195-00-7

## Safety Data Sheet

### CC-006 CRYSTAL COAT PART 2

- Flammable liquids (chapter 2.6), Cat. 3
- Eye damage/irritation (chapter 3.3), Cat. 2

H226 Flammable liquid and vapor  
H319 Causes serious eye irritation

#### 3. Urea Polymer

Concentration 5 - 10 %

#### 4. Solvent naphtha (petroleum), heavy arom

Concentration 5 - 10 %  
CAS no. 64742-94-5

- Flammable liquids (chapter 2.6), Cat. 4
- Acute toxicity, oral (chapter 3.1), Cat. 4
- Acute toxicity, dermal (chapter 3.1), Cat. 4
- Acute toxicity, inhalation (chapter 3.1), Cat. 4

H227 Combustible liquid

#### 5. XYLENES (MIXED)

Concentration < 0 - 5 %

Other names / synonyms xylene [4]; XYLENE, mixture of isomers; XYLENES,MIXED; XYLOL  
EC no. 215-535-7  
CAS no. 1330-20-7  
Index no. 601-022-00-9

- Flammable liquids (chapter 2.6), Cat. 3
- Acute toxicity (chapter 3.1), Cat. 4
- Skin corrosion/irritation (chapter 3.2), Cat. 2

H226 Flammable liquid and vapor  
H312 Harmful in contact with skin  
H315 Causes skin irritation  
H332 Harmful if inhaled

#### 6. TRIETHYLAMINE

Concentration < 0 - 5 %

Other names / synonyms Ethanamine, N,N-diethyl-; N,N-DIETHYLETHANAMINE; TEN;  
TRIETHYLAMINE (DOT)  
EC no. 204-469-4  
CAS no. 121-44-8  
Index no. 612-004-00-5

- Flammable liquids (chapter 2.6), Cat. 2
- Acute toxicity (chapter 3.1), Cat. 4
- Skin corrosion/irritation (chapter 3.2), Cat. 1A

H225 Highly flammable liquid and vapor

## Safety Data Sheet

### CC-006 CRYSTAL COAT PART 2

H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H332	Harmful if inhaled

#### 7. NAPHTHALENE

Concentration 0.82 %

Other names / synonyms	NAPHTHENE
EC no.	202-049-5
CAS no.	91-20-3
Index no.	601-052-00-2

- Carcinogenicity (chapter 3.6), Cat. 2
- Acute toxicity (chapter 3.1), Cat. 4
- Hazardous to the aquatic environment - acute hazard (chapter 4.1), Cat. 1
- Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 1

H302	Harmful if swallowed
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

#### 8. ISOPROPANOL

Concentration < 0 - 5 %

Other names / synonyms	2-PROPANOL; 2-PROPYL ALCOHOL; ISOPROPYL ALCOHOL
EC no.	414-810-0
CAS no.	67-63-0
Index no.	607-403-00-6

- Flammable liquids (chapter 2.6), Cat. 2
- Eye damage/irritation (chapter 3.3), Cat. 2A
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

H225	Highly flammable liquid and vapor
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

#### 9. Component 9 (trade secret)

Concentration < 0 - 5 %

#### 10. p-toluenesulphonic acid (containing a maximum of 5 % H<sub>2</sub>SO<sub>4</sub>)

Concentration < 0 - 1 %

Other names / synonyms	Benzenesulfonic acid, 4-methyl-;
EC no.	203-180-0
CAS no.	104-15-4
Index no.	016-030-00-2

- Eye damage/irritation (chapter 3.3), Cat. 2
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

- Skin corrosion/irritation (chapter 3.2), Cat. 2

H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

### 11. 1,2,4-Trimethylbenzene

Concentration < 0 - 1 %

Other names / synonyms Benzene, 1,2,4-trimethyl-; Pseudocumene; TRIMETHYLBENZ;  
Trimethylbenzene,1,2,4-

EC no.	202-436-9
CAS no.	95-63-6
Index no.	601-043-00-3

- Flammable liquids (chapter 2.6), Cat. 3  
- Acute toxicity (chapter 3.1), Cat. 4  
- Eye damage/irritation (chapter 3.3), Cat. 2  
- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3  
- Skin corrosion/irritation (chapter 3.2), Cat. 2  
- Hazardous to the aquatic environment - long-term hazard (chapter 4.1), Cat. 2

H226	Flammable liquid and vapor
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H411	Toxic to aquatic life with long lasting effects

### 12. Formaldehyde (solution)

Concentration 0.02 %

Other names / synonyms Formaldehyde; formaldehyde ...%;

EC no.	200-001-8
CAS no.	50-00-0
Index no.	605-001-00-5

- Carcinogenicity (chapter 3.6), Cat. 2  
- Acute toxicity (chapter 3.1), Cat. 3  
- Skin corrosion/irritation (chapter 3.2), Cat. 1B  
- Sensitization, skin (chapter 3.4), Cat. 1

H301	Toxic if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H331	Toxic if inhaled
H351	Suspected of causing cancer

---

## SECTION 4: First-aid measures

### 4.1 Description of necessary first-aid measures

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

General advice	Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	If breathed in, move person into fresh air. If not breathing, give artificial respiration.
In case of skin contact	Wash off with soap and plenty of water.
In case of eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
If swallowed	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
Personal protective equipment for first-aid responders	Wear self-contained breathing apparatus for firefighting if necessary.

### 4.2 Most important symptoms/effects, acute and delayed

The most important known symptoms and effects are described in section 3.

### 4.3 Indication of immediate medical attention and special treatment needed, if necessary

No data available.

---

## SECTION 5: Fire-fighting measures

### 5.1 Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Specific hazards arising from the chemical

Carbon oxides

### 5.3 Special protective actions for fire-fighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### Further information

Use water spray to cool unopened containers.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

#### Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Use explosion-proof equipment. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Specific end use(s)

Apart from the uses mentioned in section 1.3 no other specific uses are stipulated.

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### 1. 2-methoxy-1-methylethyl acetate (CAS: 108-65-6 EC: 203-603-9)

TWA (Inhalation): 100 ppm

#### 2. Solvent naphtha (petroleum), heavy arom (CAS: 64742-94-5)

TWA (Inhalation): 100 MG/M3

#### 3. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 4. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 435 mg/m3 (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 5. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

PEL (Inhalation): 100 ppm, (ST) 150 ppm, (C) 300 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 6. Xylenes (o-, m-, p-isomers) (CAS: 1330-20-7)

REL (Inhalation): 100 ppm, (ST) 150 ppm (NIOSH)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 7. Triethylamine (CAS: 121-44-8)

PEL (Inhalation): 25 ppm (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 8. Triethylamine (CAS: 121-44-8)

PEL (Inhalation): 100 mg/m3 (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 9. Triethylamine (CAS: 121-44-8)

PEL (Inhalation): (C) 1 ppm (Cal/OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 10. Triethylamine (CAS: 121-44-8)

REL (Inhalation): See Appendix D (NIOSH)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 11. Naphthalene (CAS: 91-20-3)

PEL (Inhalation): 10 ppm (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 12. Naphthalene (CAS: 91-20-3)

PEL (Inhalation): 50 mg/m3 (OSHA)

OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

## Safety Data Sheet

### CC-006 CRYSTAL COAT PART 2

#### 13. Naphthalene (CAS: 91-20-3)

PEL (Inhalation): 10 ppm, (ST) 15 ppm (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 14. Naphthalene (CAS: 91-20-3)

REL (Inhalation): 10 ppm, (ST) 15 ppm (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 15. Isopropyl alcohol (CAS: 67-63-0)

PEL (Inhalation): 400 ppm (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 16. Isopropyl alcohol (CAS: 67-63-0)

PEL (Inhalation): 980 mg/m<sup>3</sup> (OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 17. Isopropyl alcohol (CAS: 67-63-0)

PEL (Inhalation): 400 ppm, (ST) 500 ppm (Cal/OSHA)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 18. Isopropyl alcohol (CAS: 67-63-0)

REL (Inhalation): 400 ppm, (ST) 500 ppm (NIOSH)  
OSHA Annotated Table Z-1, [www.osha.gov](http://www.osha.gov)

#### 19. 1,2,4-Trimethylbenzene (CAS: 95-63-6 EC: 202-436-9)

TWA (Inhalation): 25 ppm 125mg/m<sup>3</sup> (NIOSH)

#### 20. Formaldehyde (CAS: 50-00-0 EC: 200-001-8)

PEL-C (Inhalation): 0.3 ppm (ACGIH)  
USA. ACGIH Threshold Limit Values (TLV)

#### 21. Formaldehyde (CAS: 50-00-0 EC: 200-001-8)

Remarks: Upper Respiratory Tract irritation, Eye irritation, Suspected human carcinogen, Sensitizer

#### 22. Formaldehyde (CAS: 50-00-0 EC: 200-001-8)

PEL-TWA (Inhalation): 0.016 ppm (NIOSH)  
USA. NIOSH Recommended Exposure Limits

#### 23. Formaldehyde (CAS: 500-00-0 EC: 200-001-8)

Potential Occupational Carcinogen  
See Appendix A

#### 24. Formaldehyde (CAS: 50-00-0 EC: 200-001-8)

PEL-C (Inhalation): 0.1 ppm (NIOSH)  
USA. NIOSH Recommended Exposure Limits

#### 25. Formaldehyde (CAS: 50-00-0 EC: 200-001-8)

1910.1048: This standard applies to all occupational exposures to formaldehyde, i.e. from formaldehyde gas, its solutions, and materials that release formaldehyde OSHA specifically regulated carcinogen

#### 26. Formaldehyde (CAS: 50-00-0 EC: 200-001-8)

0.75 ppm  
OSHA Specifically Regulated Chemicals/Carcinogens

### 8.2 Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### 8.3 Individual protection measures, such as personal protective equipment (PPE)

#### Eye/face protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### Body protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### Respiratory protection

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### Thermal hazards

Thermal breakdown during fire or very high heat conditions may release Carbon Oxides, formaldehyde, silicon dioxide and incompletely burnt hydrocarbons.

### Environmental exposure controls

Do not let product enter drains.

---

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance/form	Viscous Liquid
Odor	Characteristist Solvent Odor
Odor threshold	No Data
pH	No Data
Melting point/freezing point	No Data
Initial boiling point and boiling range	No Data
Flash point	95 F
Evaporation rate	Slower than Ether
Flammability (solid, gas)	
Upper/lower flammability limits	24.6
Upper/lower explosive limits	.6
Vapor pressure	No Data
Vapor density	Heavier than Air
Relative density	8.99 lbs
Solubility(ies)	None Soluable
Partition coefficient: n-octanol/water	No Data
Auto-ignition temperature	No Data
Decomposition temperature	No Data
Viscosity	No Data
Explosive properties	No Data
Oxidizing properties	

### Other safety information

VOC WEIGHT 38.80%  
VOC VOLUME 45.57%  
VOC 3.48 LBS/GAL

---

## SECTION 10: Stability and reactivity

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

### 10.1 Reactivity

This product has not been tested as a mixture, see Section 3: Hazards Identification

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

None anticipated during normal use and storage.

### 10.4 Conditions to avoid

Heat, flames and sparks.

### 10.5 Incompatible materials

Bases, amines, alkali metals, metals, permanganates, e.g. potassium permanganate, fluorine, metal acetylides, hexalithium disilicide

### 10.6 Hazardous decomposition products

This product has not been tested as a mixture, see Section 3: Hazards Identification

---

## SECTION 11: Toxicological information

### Information on toxicological effects

#### Acute toxicity

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Skin corrosion/irritation

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Serious eye damage/irritation

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Respiratory or skin sensitization

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Germ cell mutagenicity

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Carcinogenicity

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Reproductive toxicity

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Summary of evaluation of the CMR properties

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### STOT-single exposure

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### STOT-repeated exposure

This product has not been tested as a mixture, see Section 3: Hazards Identification

#### Aspiration hazard

This product has not been tested as a mixture, see Section 3: Hazards Identification

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

### Additional information

This product has not been tested as a mixture, see Section 3: Hazards Identification

---

## SECTION 12: Ecological information

### Toxicity

This product has not been tested as a mixture, see Section 3: Hazards Identification

### Persistence and degradability

This product has not been tested as a mixture, see Section 3: Hazards Identification

### Bioaccumulative potential

This product has not been tested as a mixture, see Section 3: Hazards Identification

### Mobility in soil

This product has not been tested as a mixture, see Section 3: Hazards Identification

### Results of PBT and vPvB assessment

This product has not been tested as a mixture, see Section 3: Hazards Identification

### Other adverse effects

This product has not been tested as a mixture, see Section 3: Hazards Identification

---

## SECTION 13: Disposal considerations

### Disposal of the product

Dispose of in accordance with local, county, state, provincial and federal regulations. Emptied containers may retain hazardous properties. Empty containers should be disposed of in an environmentally safe manner in accordance with applicable local regulations.

### Disposal of contaminated packaging

Dispose of as unused product properly.

### Waste treatment

Not Applicable

### Sewage disposal

Not Applicable

### Other disposal recommendations

Dispose of in accordance with local, county, state, provincial and federal regulations. Emptied containers may retain hazardous properties. Empty containers should be disposed of in an environmentally safe manner in accordance with applicable local regulations.

---

## SECTION 14: Transport information

### DOT (US)

UN Number: 1210

Class:3

Packing Group: III

Proper Shipping Name: Printing Ink

Reportable quantity (RQ):

Marine pollutant:

Poison inhalation hazard:

# Safety Data Sheet

## CC-006 CRYSTAL COAT PART 2

### IMDG

UN Number: 1210  
Class: 3  
Packing Group: III  
EMS Number:  
Proper Shipping Name: Printing Ink

### IATA

UN Number: 1210  
Class: 3  
Packing Group: III  
Proper Shipping Name: Printing Ink

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### SARA 302 Components

Formaldehyde

#### SARA 311/312 Hazards

Formaldehyde, Naphthalene, 1,2,4- Trimethylbenzene, Xylene, Ethylbenzene, Triethylamine, Isopropyl Alcohol

#### SARA 313 Components

Formaldehyde, Naphthalene, 1,2,4- Trimethylbenzene, Isopropyl Alcohol

#### New Jersey Right To Know Components

Formaldehyde, Naphthalene, 2-methoxy-1-methylethyl acetate, Solvent naphtha (petroleum), heavy arom, Naphthalene, 1,2,4- Trimethylbenzene, Xylene, Ethylbenzene, Triethylamine, Isopropyl Alcohol, p-TOLUENE SULFONIC ACID

#### Massachusetts Right To Know Components

Formaldehyde, 2-methoxy-1-methylethyl acetate, Solvent naphtha (petroleum), heavy arom, Naphthalene, 1,2,4- Trimethylbenzene, Xylene, Ethylbenzene, Triethylamine, Isopropyl Alcohol, p-TOLUENE SULFONIC ACID

#### Pennsylvania Right To Know Components

Formaldehyde, 2-methoxy-1-methylethyl acetate, Solvent naphtha (petroleum), heavy arom, Naphthalene, 1,2,4- Trimethylbenzene, Xylene, Ethylbenzene, Triethylamine, Isopropyl Alcohol, p-TOLUENE SULFONIC ACID

#### California Prop. 65 components


Chemical name: XYLENES (MIXED), Naphthalene, Formaldehyde, Ethylbenzene

#### HMIS Rating

CC-006 CRYSTAL COAT PART 2	
HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

#### NFPA Rating

**Safety Data Sheet**  
**CC-006 CRYSTAL COAT PART 2**



---

**SECTION 16: Other information**

**16.2 Preparation information**

The information and recommendations contained in this Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the SDS was prepared. No warranty, guarantee or representation is made. The user of this product must decide what safety measures are necessary to safely use this product either alone or in combination with other products and determine its environmental regulatory compliance obligations under any federal, state or local laws.